



# Technical Data Sheet

6/2/2006

Product: **9500**

| <u>Physical Property</u>         | <u>Value</u>         | <u>Test Method</u> |
|----------------------------------|----------------------|--------------------|
| Color                            | Green                |                    |
| Density (lbs / ft3)              | 2.6 - 2.8            | ASTM D-3574-01     |
| Indent Force Deflection<br>@ 25% | 27 - 33              | ASTM D-3574-01     |
| Compression Set at 50% comp.(%)  | 10                   | ASTM D-3574-01     |
| Tensile Strength (psi)           | 10                   | ASTM D-3574-01     |
| Tear Strength (lbs/lin inch)     | 1.0                  | ASTM D-3574-01     |
| Elongation (%)                   | 100                  | ASTM D-3574-01     |
| Flame Resistance                 | pass                 | Cal 117            |
| Other Properties                 | High Resiliency Foam |                    |

This information is based on actual testing in a controlled environment. However, as conditions of use are not within our control, Amcon does not guarantee from use of such products or other information herein; no warranty expressed or implied is given. It is the user's responsibility to determine the appropriateness of the products for their specific end uses.

**WARNING: URETHANE FOAM IS FLAMMABLE!**  
**Urethane Foam should not be exposed to open flame or other ignition sources.**  
**Urethanes burn rapidly with great heat and release gases which are extremely hazardous.**

5360 Main St. NE Minneapolis, MN 55421

Ph. 888-360-8050

**[www.amconfoam.com](http://www.amconfoam.com)**